



Close this window

MSDS

**Common Name:** PVTLBL SSPR 6PK TG ENAML ULTRA FLAT BLCK

**Manufacturer:** W.W. GRAINGER

**MSDS Revision Date:** 1/11/2010

**MSDS Format:** No Format Specified

**Grainger Item Number(s):** 4WGC1

**Manufacturer Model Number(s):**

### MSDS Table of Contents

Click the desired link below to jump directly to that section in the MSDS.

[SECTION 1 - CHEMICAL PRODUCT / COMPANY INFORMATION](#)  
[SECTION 2 - COMPOSITION / INFORMATION ON INGREDIENTS](#)  
[SECTION 3 - HAZARDS IDENTIFICATION](#)  
[SECTION 4 - FIRST AID MEASURES](#)  
[SECTION 5 - FIRE FIGHTING MEASURES](#)  
[SECTION 6 - ACCIDENTAL RELEASE MEASURES](#)  
[SECTION 7 - HANDLING AND STORAGE](#)  
[SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION](#)  
[SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES](#)  
[SECTION 10 - STABILITY AND REACTIVITY](#)  
[SECTION 11 - TOXICOLOGICAL INFORMATION](#)  
[SECTION 12 - ECOLOGICAL INFORMATION](#)  
[SECTION 13 - DISPOSAL INFORMATION](#)  
[SECTION 14 - TRANSPORTATION INFORMATION](#)  
[SECTION 15 - REGULATORY INFORMATION](#)  
[SECTION 16 - OTHER INFORMATION](#)

MATERIAL SAFETY DATA SHEET

24 HOUR ASSISTANCE: 800-228-5635

## SECTION 1 - CHEMICAL PRODUCT / COMPANY INFORMATION



PRODUCT NAME: PVTLBL SSPR 6PK TG ENAML ULTRA FLAT BLCK

IDENTIFICATION NUMBER: 251834

PRODUCT USE/CLASS: TOUGH GUY AEROSOLS 4WGC1

**SUPPLIER:**

W.W. GRAINGER  
100 GRAINGER PARKWAY  
LAKE FOREST, IL 60045-5201  
USA

**MANUFACTURER:**

W.W. GRAINGER  
100 GRAINGER PARKWAY  
LAKE FOREST, IL 60045-5201  
USA

PREPARER: REGULATORY DEPARTMENT

REVISION DATE: 01/11/2010

**SECTION 2 - COMPOSITION / INFORMATION ON INGREDIENTS**

CHEMICAL NAME	CAS NUMBER	WEIGHT % LESS THAN	ACGIH TLV-TWA	ACGIH TLV-STEL	OSHA PEL-TWA	OSHA PEL CEILING
ACETONE	67-64-1	35.0	500 PPM	750 PPM	1000 PPM	N.E.
LIQUEFIED PETROLEUM GAS	68476-86-8	30.0	N.E.	N.E.	N.E.	N.E.
MINERAL SPIRITS	64742-88-7	10.0	100 PPM	N.E.	100 PPM	N.E.
ALIPHATIC HYDROCARBON	64742-89-8	10.0	N.E.	N.E.	300 PPM	N.E.
XYLENE	1330-20-7	5.0	100 PPM	150 PPM	100 PPM	N.E.
NAPHTHA	8032-32-4	5.0	N.E.	N.E.	N.E.	N.E.
MAGNESIUM SILICATE	14807-96-6	5.0	2 MG/M3	N.E.	0.1 MG/M3 (RESPIRABLE)	N.E.
PIGMENT BLACK 7	1333-86-4	5.0	3.5 MG/M3	N.E.	3.5 MG/M3	N.E.
ETHYL-BENZENE	100-41-4	5.0	100 PPM	125 PPM	100 PPM	N.E.

**SECTION 3 - HAZARDS IDENTIFICATION****EMERGENCY OVERVIEW:**

CONTENTS UNDER PRESSURE. HARMFUL IF INHALED. MAY AFFECT THE BRAIN OR NERVOUS SYSTEM CAUSING DIZZINESS, HEADACHE OR NAUSEA. VAPORS MAY CAUSE FLASH FIRE OR EXPLOSION. HARMFUL IF SWALLOWED. EXTREMELY FLAMMABLE LIQUID AND VAPOR.

EFFECTS OF OVEREXPOSURE - EYE CONTACT: CAUSES EYE IRRITATION.

**EFFECTS OF OVEREXPOSURE - SKIN CONTACT:**

PROLONGED OR REPEATED CONTACT MAY CAUSE SKIN IRRITATION. SUBSTANCE MAY CAUSE SLIGHT SKIN IRRITATION.

**EFFECTS OF OVEREXPOSURE - INHALATION:**

HIGH VAPOR CONCENTRATIONS ARE IRRITATING TO THE EYES, NOSE, THROAT AND LUNGS. AVOID BREATHING VAPORS OR MISTS. HIGH GAS, VAPOR, MIST OR DUST CONCENTRATIONS MAY BE HARMFUL IF INHALED. HARMFUL IF INHALED.

**EFFECTS OF OVEREXPOSURE - INGESTION:**

ASPIRATION HAZARD IF SWALLOWED; CAN ENTER LUNGS AND CAUSE DAMAGE. SUBSTANCE MAY BE HARMFUL IF SWALLOWED.

**EFFECTS OF OVEREXPOSURE - CHRONIC HAZARDS:**

IARC LISTS ETHYLBENZENE AS A POSSIBLE HUMAN CARCINOGEN (GROUP 2B). MAY CAUSE CENTRAL NERVOUS SYSTEM DISORDER (E.G., NARCOSIS INVOLVING A LOSS OF COORDINATION, WEAKNESS, FATIGUE, MENTAL CONFUSION, AND BLURRED VISION) AND/OR DAMAGE. REPORTS HAVE ASSOCIATED REPEATED AND PROLONGED OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. OVEREXPOSURE TO XYLENE IN LABORATORY ANIMALS HAS BEEN ASSOCIATED WITH LIVER ABNORMALITIES, KIDNEY, LUNG, SPLEEN, EYE AND BLOOD DAMAGE AS WELL

AS REPRODUCTIVE DISORDERS. EFFECTS IN HUMANS, DUE TO CHRONIC OVEREXPOSURE, HAVE INCLUDED LIVER, CARDIAC ABNORMALITIES AND NERVOUS SYSTEM DAMAGE.

CONTAINS CARBON BLACK. CHRONIC INFLAMMATION, LUNG FIBROSIS, AND LUNG TUMORS HAVE BEEN OBSERVED IN SOME RATS EXPERIMENTALLY EXPOSED FOR LONG PERIODS OF TIME TO EXCESSIVE CONCENTRATIONS OF CARBON BLACK AND SEVERAL INSOLUBLE FINE DUST PARTICLES. TUMORS HAVE NOT BEEN OBSERVED IN OTHER ANIMAL SPECIES (I.E., MOUSE AND HAMSTER) UNDER SIMILAR CIRCUMSTANCES AND STUDY CONDITIONS. EPIDEMIOLOGICAL STUDIES OF NORTH AMERICAN WORKERS SHOW NO EVIDENCE OF CLINICALLY SIGNIFICANT ADVERSE HEALTH EFFECTS DUE TO OCCUPATIONAL EXPOSURE TO CARBON BLACK.

CARBON BLACK IS LISTED AS A GROUP 2B-"POSSIBLY CARCINOGENIC TO HUMANS" BY IARC AND IS PROPOSED TO BE LISTED AS A4- "NOT CLASSIFIED AS A HUMAN CARCINOGEN" BY THE AMERICAN CONFERENCE OF GOVERNMENTAL INDUSTRIAL HYGIENISTS. SIGNIFICANT EXPOSURE IS NOT ANTICIPATED DURING BRUSH APPLICATION OR DRYING. RISK OF OVEREXPOSURE DEPENDS ON DURATION AND LEVEL OF EXPOSURE TO DUST FROM REPEATED SANDING OF SURFACES OR SPRAY MIST AND THE ACTUAL CONCENTRATION OF CARBON BLACK IN THE FORMULA.

PRIMARY ROUTE(S) OF ENTRY:

SKIN CONTACT, SKIN ABSORPTION, INHALATION, INGESTION, EYE CONTACT

#### **SECTION 4 - FIRST AID MEASURES**



FIRST AID - EYE CONTACT:

IMMEDIATELY FLUSH EYES WITH PLENTY OF WATER FOR AT LEAST 15 MINUTES HOLDING EYELIDS OPEN. GET MEDICAL ATTENTION. DO NOT ALLOW RUBBING OF EYES OR KEEPING EYES CLOSED.

FIRST AID - SKIN CONTACT:

WASH WITH SOAP AND WATER. GET MEDICAL ATTENTION IF IRRITATION DEVELOPS OR PERSISTS.

FIRST AID - INHALATION:

IF YOU EXPERIENCE DIFFICULTY IN BREATHING, LEAVE THE AREA TO OBTAIN FRESH AIR. IF CONTINUED DIFFICULTY IS EXPERIENCED, GET MEDICAL ASSISTANCE IMMEDIATELY.

FIRST AID - INGESTION:

ASPIRATION HAZARD:

DO NOT INDUCE VOMITING OR GIVE ANYTHING BY MOUTH BECAUSE THIS MATERIAL CAN ENTER THE LUNGS AND CAUSE SEVERE LUNG DAMAGE. GET IMMEDIATE MEDICAL ATTENTION.

#### **SECTION 5 - FIRE FIGHTING MEASURES**



FLASH POINT (SETAFLASH): -156 F

LOWER EXPLOSIVE LIMIT: 0.7%

UPPER EXPLOSIVE LIMIT: 12.8%

EXTINGUISHING MEDIA:

FILM FORMING FOAM, CARBON DIOXIDE, DRY CHEMICAL, WATER FOG

UNUSUAL FIRE AND EXPLOSION HAZARDS:

WATER SPRAY MAY BE INEFFECTIVE. CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. VAPORS MAY FORM EXPLOSIVE MIXTURES WITH AIR. VAPORS CAN TRAVEL TO A SOURCE OF IGNITION AND FLASH BACK.

FLASH POINT IS LESS THAN 20 DEG. .F. - EXTREMELY FLAMMABLE LIQUID AND VAPOR!

KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT,

SPARKS AND OPEN FLAME. PERFORATION OF THE PRESSURIZED CONTAINER MAY CAUSE BURSTING OF THE CAN.

SPECIAL FIREFIGHTING PROCEDURES:  
EVACUATE AREA AND FIGHT FIRE FROM A SAFE DISTANCE.

## SECTION 6 - ACCIDENTAL RELEASE MEASURES



STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED:  
CONTAIN SPILLED LIQUID WITH SAND OR EARTH. DO NOT USE COMBUSTIBLE MATERIALS SUCH AS SAWDUST. DISPOSE OF ACCORDING TO LOCAL, STATE (PROVINCIAL) AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS. REMOVE ALL SOURCES OF IGNITION, VENTILATE AREA AND REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

## SECTION 7 - HANDLING AND STORAGE



HANDLING:  
WASH THOROUGHLY AFTER HANDLING. FOLLOW ALL MSDS/LABEL PRECAUTIONS EVEN AFTER CONTAINER IS EMPTIED BECAUSE IT MAY RETAIN PRODUCT RESIDUES. AVOID BREATHING VAPOR OR MIST. USE ONLY IN A WELL-VENTILATED AREA. WASH HANDS BEFORE EATING.

STORAGE:  
KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMENT, SPARKS AND OPEN FLAME. DO NOT STORE ABOVE 120 DEG. F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS I FLAMMABLE LIQUIDS. CONTENTS UNDER PRESSURE. DO NOT EXPOSE TO HEAT OR STORE ABOVE 120 DEG. F.

## SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION



ENGINEERING CONTROLS:  
PREVENT BUILD-UP OF VAPORS BY OPENING ALL DOORS AND WINDOWS TO ACHIEVE CROSS-VENTILATION. USE PROCESS ENCLOSURES, LOCAL EXHAUST VENTILATION, OR OTHER ENGINEERING CONTROLS TO CONTROL AIRBORNE LEVELS BELOW RECOMMENDED EXPOSURE LIMITS. USE EXPLOSION-PROOF VENTILATION EQUIPMENT.

RESPIRATORY PROTECTION:  
A RESPIRATORY PROTECTION PROGRAM THAT MEETS OSHA 1910.134 AND ANSI Z88.2 REQUIREMENTS MUST BE FOLLOWED WHENEVER WORKPLACE CONDITIONS WARRANT A RESPIRATOR'S USE. A NIOSH/MSHA APPROVED AIR PURIFYING RESPIRATOR WITH AN ORGANIC VAPOR CARTRIDGE OR CANISTER MAY BE PERMISSIBLE UNDER CERTAIN CIRCUMSTANCES WHERE AIRBORNE CONCENTRATIONS ARE EXPECTED TO EXCEED EXPOSURE LIMITS.

PROTECTION PROVIDED BY AIR PURIFYING RESPIRATORS IS LIMITED. USE A POSITIVE PRESSURE AIR SUPPLIED RESPIRATOR IF THERE IS ANY POTENTIAL FOR AN UNCONTROLLED RELEASE, EXPOSURE LEVELS ARE NOT KNOWN, OR IN ANY OTHER CIRCUMSTANCES WHERE AIR PURIFYING RESPIRATORS MAY NOT PROVIDE ADEQUATE PROTECTION.

SKIN PROTECTION:  
USE IMPERVIOUS GLOVES TO PREVENT SKIN CONTACT AND ABSORPTION OF THIS MATERIAL THROUGH THE SKIN. NITRILE OR NEOPRENE GLOVES MAY AFFORD ADEQUATE SKIN PROTECTION.

EYE PROTECTION:  
USE SAFETY EYEWEAR DESIGNED TO PROTECT AGAINST SPLASH OF LIQUIDS.

OTHER PROTECTIVE EQUIPMENT:  
REFER TO SAFETY SUPERVISOR OR INDUSTRIAL HYGIENIST FOR FURTHER INFORMATION

REGARDING PERSONAL PROTECTIVE EQUIPMENT AND ITS APPLICATION.

HYGIENIC PRACTICES:

WASH THOROUGHLY WITH SOAP AND WATER BEFORE EATING, DRINKING OR SMOKING.

## SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES



BOILING RANGE: -34 - 999 F

VAPOR DENSITY: HEAVIER THAN AIR

ODOR: SOLVENT LIKE

ODOR THRESHOLD: N.E.

APPEARANCE: AEROSOLIZED MIST

EVAPORATION RATE: FASTER THAN ETHER

SOLUBILITY IN H2O: SLIGHT

FREEZE POINT: N.D.

SPECIFIC GRAVITY: 0.760

VAPOR PRESSURE: N.D.

pH: N.A.

PHYSICAL STATE: LIQUID

(SEE SECTION 16 FOR ABBREVIATION LEGEND)

## SECTION 10 - STABILITY AND REACTIVITY



CONDITIONS TO AVOID:

AVOID TEMPERATURES ABOVE 120 DEG. F. AVOID ALL POSSIBLE SOURCES OF IGNITION.

INCOMPATIBILITY:

INCOMPATIBLE WITH STRONG OXIDIZING AGENTS, STRONG ACIDS AND STRONG ALKALIES.

HAZARDOUS DECOMPOSITION:

WHEN HEATED TO DECOMPOSITION, IT EMITS ACRID SMOKE AND IRRITATING FUMES. BY OPEN FLAME, CARBON MONOXIDE AND CARBON DIOXIDE.

HAZARDOUS POLYMERIZATION: WILL NOT OCCUR UNDER NORMAL CONDITIONS.

STABILITY: THIS PRODUCT IS STABLE UNDER NORMAL STORAGE CONDITIONS.

## SECTION 11 - TOXICOLOGICAL INFORMATION



PRODUCT LD50: N.D.

PRODUCT LC50: N.D.

CHEMICAL NAME	LD50	LC50
ACETONE	5800 MG/KG (RAT)	50100 MG/M3 (RAT, 8HR)
LIQUEFIED PETROLEUM GAS	N.E.	N.E.

MINERAL SPIRITS	>8 MG/KG (RAT, ORAL)	>1400 PPM (RAT, INHALATION, 4HR)
ALIPHATIC HYDROCARBON	>5000 MG/KG (RAT, ORAL)	N.E.
XYLENE	4300 MG/KG (RAT, ORAL)	5000 PPM (RAT, INHALATION, 4HR)
NAPHTHA	>5000 MG/KG (RAT, ORAL)	N.E.
MAGNESIUM SILICATE	N.E.	TCLO: 11 MG/M3 (INHALATION)
PIGMENT BLACK 7	>8000 MG/KG (RAT, ORAL)	N.E.
ETHYLBENZENE	3500 MG/KG (RAT, ORAL)	N.E.

## SECTION 12 - ECOLOGICAL INFORMATION



ECOLOGICAL INFORMATION: PRODUCT IS A MIXTURE OF LISTED COMPONENTS.

## SECTION 13 - DISPOSAL INFORMATION



DISPOSAL INFORMATION:  
DISPOSE OF MATERIAL IN ACCORDANCE TO LOCAL, STATE AND FEDERAL REGULATIONS AND ORDINANCES. DO NOT ALLOW TO ENTER STORM DRAINS OR SEWER SYSTEMS.

## SECTION 14 - TRANSPORTATION INFORMATION



DOT PROPER SHIPPING NAME: CONSUMER COMMODITY

DOT TECHNICAL NAME: N.A.

DOT UN/NA NUMBER: N.A.

DOT HAZARD CLASS: ORM-D

PACKING GROUP: N.A.

HAZARD SUBCLASS: N.A.

RESP. GUIDE PAGE: 126

## SECTION 15 - REGULATORY INFORMATION



CERCLA - SARA HAZARD CATEGORY:

THIS PRODUCT HAS BEEN REVIEWED ACCORDING TO THE EPA "HAZARD CATEGORIES" PROMULGATED UNDER SECTIONS 311 AND 312 OF THE SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 (SARA TITLE III) AND IS CONSIDERED, UNDER APPLICABLE DEFINITIONS, TO MEET THE FOLLOWING CATEGORIES:  
IMMEDIATE HEALTH HAZARD, CHRONIC HEALTH HAZARD, FIRE HAZARD, PRESSURIZED GAS HAZARD

SARA SECTION 313:

LISTED BELOW ARE THE SUBSTANCES (IF ANY) CONTAINED IN THIS PRODUCT THAT ARE SUBJECT TO THE REPORTING REQUIREMENTS OF SECTION 313 OF TITLE III OF THE SUPERFUND AMENDMENT AND REAUTHORIZATION ACT OF 1986 AND

40 CFR PART 372:

CHEMICAL NAME	CAS NUMBER
XYLENE	1330-20-7
ETHYLBENZENE	100-41-4

TOXIC SUBSTANCES CONTROL ACT:

LISTED BELOW ARE THE SUBSTANCES (IF ANY) CONTAINED IN THIS PRODUCT THAT ARE SUBJECT TO THE REPORTING REQUIREMENTS OF TSCA 12(B) IF EXPORTED FROM THE UNITED STATES:

U.S. STATE REGULATIONS: AS FOLLOWS

NEW JERSEY RIGHT-TO-KNOW:  
THE FOLLOWING MATERIALS ARE NON-HAZARDOUS, BUT ARE AMONG THE TOP FIVE COMPONENTS IN THIS PRODUCT.

CHEMICAL NAME	CAS NUMBER
MODIFIED ALKYD	PROPRIETARY

PENNSYLVANIA RIGHT-TO-KNOW:  
THE FOLLOWING NON-HAZARDOUS INGREDIENTS ARE PRESENT IN THE PRODUCT AT GREATER THAN 3%.

CHEMICAL NAME	CAS NUMBER
MODIFIED ALKYD	PROPRIETARY
CALCIUM CARBONATE	1317-65-3

CALIFORNIA PROPOSITION 65:

WARNING!

THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN BY THE STATE OF CALIFORNIA TO CAUSE CANCER.

WARNING!

THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

INTERNATIONAL REGULATIONS: AS FOLLOWS

CANADIAN WHMIS:  
THIS MSDS HAS BEEN PREPARED IN COMPLIANCE WITH CONTROLLED PRODUCT REGULATIONS EXCEPT FOR THE USE OF THE 16 HEADINGS.

CANADIAN WHMIS CLASS:  
AB5  
D2A  
D2B

## SECTION 16 - OTHER INFORMATION



HMIS RATINGS:  
HEALTH 2\*  
FLAMMABILITY 4  
REACTIVITY 0  
PERSONAL PROTECTION X

REASON FOR REVISION: REGULATORY UPDATE

LEGEND:

N.A. - NOT APPLICABLE  
N.E. - NOT ESTABLISHED  
N.D. - NOT DETERMINED

THE INFORMATION CONTAINED ON THIS MSDS HAS BEEN CHECKED AND SHOULD BE ACCURATE. HOWEVER, IT IS THE RESPONSIBILITY OF THE USER TO COMPLY WITH ALL FEDERAL, STATE, AND LOCAL LAWS AND REGULATIONS.